

SPF 50^a sunscreen spray with Eastman AQ™ 38S polymer

Part	Product Name	Wt%	Ingredient/INCI name	Manufacturer
A	Deionized water	51.32	Water (aqua)	—
	AMPHISOL® K	2.5	Potassium cetyl phosphate	DSM
	Glycerin	3.0	Glycerin	VVF
	EDETA® BD	0.05	Disodium EDTA	BASF
	Eastman AQ™ 38S polymer	3.0	Polyester-5	Eastman
B	Crodamol™ AB	5.0	C12-15 alkyl benzoate	Croda
	PARSOL® MCX	7.5	Ethylhexyl methoxycinnamate	DSM
	PARSOL® 340	4.0	Octocrylene	DSM
	Uvinul® M 40	6.0	Benzophenone-3	BASF
	Z-Cote® HP	1.43	Zinc oxide (and) triethoxycaprylsilane	BASF
	Neo Heliopan® HMS	8.0	Homosalate	Symrise
	Eusolex® OS	5.0	Ethylhexyl salicylate	EMD
	Cutina® GMS	2.0	Glyceryl stearate	BASF
Lanette® O	1.20	Cetearyl alcohol	BASF	
C	Preservative	q.s.	—	—

^aSPF determined by *in vivo* testing.

PROCEDURE

Part A

1. Combine all part A ingredients except Eastman AQ 38S polymer, and heat to 75°C while stirring.
2. Add Eastman AQ 38S pellets at 75°C; continue stirring until pellets are completely dispersed.

continued on back »

Part B

3. Combine part B ingredients and heat to about 85°C, stirring continually until mixture is completely dissolved.
4. With part A at 75°C and part B at 85°C, gradually add part B to part A with rapid stirring. Continue stirring until the combined parts A and B pre-emulsion is homogeneous.
5. Homogenize* the combined parts A and B pre-emulsion at high speed for 10 minutes with no additional heating; cover container to prevent water loss.
6. While stirring, cool the combined parts A and B emulsion to 40°C or less.

Part C

7. Add preservative at 40°C or less while stirring. If necessary, adjust pH to 6.0–7.0 with dilute sodium hydroxide solution.

**Suitable laboratory homogenizers include rotor-stator, slotted-head mixers—with a head diameter of 4.5 cm or more—available from Silverson Machines, Inc. or Janke & Kunkel. The mean particle diameter of this homogenized emulsion is about 0.7–1.2 micron, which is in a desired range for formula stability. Since homogenizer type, homogenizer head design, and rotor speed may produce different mean particle sizes, it is up to the formulator to obtain their required particle size.*

EASTMAN
The results of insight™

Eastman Corporate Headquarters
P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626)
Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2020 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.