



# SkyKleen™ aviation solvent

A new generation aviation solvent that combines excellent cleaning performance with environmentally friendly characteristics

## Cleaning applications

- Skydrol™ removal
- Polysulfide sealant removal (cured/uncured)
- RTV removal
- Degreasing
- Carbon removal (brake and piston housings)
- Engine cleaning
- Final cleaning prior to painting and bonding
- General surface cleaning
- Carbon epoxy composite surface cleaning
- Fiberglass resin removal
- Adhesive/epoxy removal

## Environmentally friendly

- Inherently biodegradable
- Nonhalogenated
- Nonozone depleting
- Minimizes VOC emissions
- Nonhazardous waste per RCRA

## Productivity considerations

- Will not adversely affect metals
- Leaves no residue
- Slower evaporation minimizes solvent consumption
- Better penetration/minimizes waste
- Cost-effective vs. other replacement solvents

## Safety considerations

- Noncombustible (flash point = 102°C/216°F)
- Noncaustic
- Low odor
- Improved worker safety
- Nonhazardous by DOT shipping regulations

## Physical properties

- Clear, water-white liquid
- Low odor
- Distillation range: 195° to 216°C (383° to 421°F)
- Density @ 20°C (68°F): 1.09 g/mL (9.06 lb/gal)
- Viscosity @ 25°C (77°F): 3.88 cP
- Freezing point: -40°C (-40°F)
- Solubility in water: 5.5% (w/w)
- Flashpoint (Pensky-Martin CC): 99°C (210°F)
- Autoignition temperature: >400°C (>752°F)
- Vapor pressure: 0.08 hPa @ 20°C (68°F)
- AIT: 438°C (820°F)

## Qualifications

- Boeing BAC 5750, Airbus AIMS 09-03-001/IPS 09-03-001-02





**Eastman Chemical Company  
Corporate Headquarters**

P.O. Box 431  
Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626)  
Other Locations, +(1) 423-229-2000

[www.eastman.com/locations](http://www.eastman.com/locations)

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2016 Eastman Chemical Company. Eastman brands referenced herein are trademarks of Eastman Chemical Company or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.