

Liquid lipstick with Eastman Sustane™ SAIB MCT

Part	Product name	Wt%	Ingredient/INCI name	Manufacturer
A	Eutanol G	9.80	Octyldodecanol	BASF
	XIAMETER® PMX-200 Silicone Fluid	4.00	Dimethicone	Dow
	Eastman Sustane™ SAIB MCT	15.00	Sucrose acetate isobutyrate (and) caprylic/capric triglyceride	Eastman
	Crodamol™ AB	25.00	C12-15 alkyl benzoate	Croda
	Beeswax	4.00	Beeswax (cera alba)	Strahl & Pitsch
	Covi-Ox® T 50	0.20	Tocopherol	BASF
B	Titanium dioxide dispersion	5.00	Titanium dioxide (and) octyldodecanol	—
	SW50R40A	8.00	Synthetic wax (and) Red 40 Lake (and) isopropyl titanium triisostearate	Kobo Products
	XIAMETER® PMX-200 Silicone Fluid	2.00	Dimethicone	Dow
	Crodamol™ AB	10.00	C12-15 alkyl benzoate	Croda
C	Timiron® Splendid Gold	2.00	Titanium dioxide (and) mica (and) silica	EMD
	PARSOL® MCX	0.50	Ethylhexyl methoxycinnamate	DSM
	AEROSIL® R 974	4.00	Silica dimethyl silylate	Evonik Industries
	KEM EHG	0.50	Phenoxyethanol (and) ethylhexylglycerin	Akema
D	Ethylhexyl palmitate	8.00	Ethylhexyl palmitate	—
	Regalite™ R1100 CG hydrocarbon resin	2.00	Hydrogenated styrene/methylstyrene/indene copolymer	Synthomer

PROCEDURE

1. Mix part A ingredients and heat to 80°C while mixing until ingredients are completely dissolved.
2. In a separate container, add part D and heat to 100°C. Mix until all ingredients have been completely dissolved; then add to part A.
3. Add part B to the part A/D mixture. Mix until homogeneous.
4. Add part C to the part A/B/D mixture, keeping the heat at 70°C. Mix until uniform.
5. Stop heating and continue mixing until temperature reaches 45°C.



Eastman Corporate Headquarters
P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626)
Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2022 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.